



PRINTER PAT FACT SHEET

SAFETY RULES AND INSTRUCTIONS FOR PUFFER GUN

Thank you for purchasing Printer Pat's Puffer Gun. It should give many years good service but if you have any queries or problems contact me directly.

FITTING INSTRUCTIONS

Locate the pneumatic compressor on your press, this is the one with an air tank. At one end of the air tank you will see a brass quick release coupling with a blue hose plugged into it. This is the main air pressure supply hose for the press*

Holding firmly on to the hose, push the outer ring of the coupling towards the tank and the hose will pop out. Do not be alarmed by the small release of air pressure as it is only the small amount of compressed air coming back from the press. The coupling automatically shuts off the supply from the air tank.

You will notice that the Y connector has a similar end to the main supply hose - plug this into the air tank.

Plug the main line into one branch of the Y connector. I recommend that you leave the Y connector in place permanently.

Plug the puffer gun hose into the other branch of the Y connector but **DO NOT** use it until you have read this **WARNING**

COMPRESSED AIR CAN BE DANGEROUS

NEVER FOOL WITH COMPRESSED AIR
NEVER POINT THE GUN AT A PERSON - EVEN IN JEST
NEVER HOLD THE NOZZLE AGAINST THE SKIN
ALWAYS WEAR PROTECTIVE GOGGLES AND MASK WHEN USING

The Puffer Gun is an open air nozzle and will use quite a large volume of air and will rapidly drain the air tank on the compressor causing the air pump to run continuously. Providing that the pump is in good condition and has sufficient oil this should be OK but I recommend using the gun for no more than five minutes in any hour.

PRESS PARTS Kaeser compressor oil PP312

PRESS PARTS Boge compressor oil PP313

PLEASE NOTE the above recommendation since Press Parts will not under any circumstances accept liability for any loss or damage arising from the use of the Puffer Gun.

After use disconnect the Puffer Gun from its branch of the Y connector, but leave the connector in place so that the gun can simply be plugged back in when needed. Spare Y connectors are available from Press Parts so that each press can be prepared and one Puffer Gun can be used on several presses!

For more extended use the Puffer Gun should be used with a larger compressor set. Press Parts can supply suitable models on request.

*This hose is often a blue fabric covered hose and is prone to perishing and leaking. It should certainly be replaced if more than 5 years old. It just so happens that Printer Pat has a few rolls on the shelf! Quote Order code PP208

NEED HELP

PRESS PARTS 0870 240 5815

Printer Pat online e-mail: pat@pressparts.co.uk